



Simple distance measurements over long distances

Product number: 12014000



Topfeatures

- Space-saving transport due to small dimensions.
- Due to the high quality production, our measuring wheels often provide decades of service in tough daily use.

All special features at a glance

- Suitable for rollover distance measurements on construction sites and in road construction.
- The measuring wheel 12014000 is particularly suitable if a display in dm and a tolerance of 0.1 % are sufficient.
- Quality counter MADE IN GERMANY mounted directly next to the measuring wheel.
- Counter also counts backwards, subtractions are possible.
- Zero setting wheel directly next to the counter enables a quick reset.
- Integrated brake prevents unintentional falsification of the measurement result.
- Foldable guide rod, transport is made easier.
- Sturdy solid disc wheel keeps the measuring wheel securely on track and ensures maximum running smoothness.
- Running rubber is ground to exactly 160 mm diameter.
- The wheel's framework is robot-welded and guarantees for lasting quality and durability.

Description

Measuring wheels are used for measuring distances on level ground. The wheel is rolled along the measuring distance while being held forward by a guide rod. The distance travelled is displayed by means of a counter. Typical applications are: official use, road and track construction, agriculture and forestry, landscaping and everywhere where distance measurements over medium to long distances are required. Choose measuring wheels with an impeller diameter of 160 mm for rollover measurements. The quality counter records the distances in the direction of travel and subtracts against the direction of travel. This measuring wheel is equipped with a parking bracket, integrated brake as well as a foldable guide rod. We recommend the optional carrying bag as an accessory with the art. no. 12903000. NESTLE measuring wheels are always "Made in Germany".

Technical Details

Calibratability	No
Colour	Construction warning colour orange
Weight	1300 g
Wheel	Full wheel
Wheel diameter	160 mm



Measuring range	9999.9 m / dm reading
Wheel circumference	50 cm
Tolerance	0.1 %

Scope of supply

NESTLE measuring wheel, rollover measurements