

NESTLE PULSAR HV-G

Easy handling with highest precision

Product number :16017001



Topfeatures

- Including laser receiver PDRG60 with mm display.
- Set up, switch on, let's go! No tedious adjustment.
- Complete package with receiver and target plate.
- Sturdy aluminium housing
- High visibility

All special features at a glance

- A thick-walled, solid aluminium housing protects the laser during tough construction use.
- Highest quality standards in processing.
- Integrated laser diode significantly increases visibility indoors.
- The green laser beam of the PULSAR HV-G is better perceived by the human eye.
- Total range of a good 500 m.
- The laser can also be operated vertically.

Description

The PULSAR HV-G is a robust yet accurate multifunction laser with three working modes: rotation, scan line and point mode. In addition, the HV-G can be manually tilted in two axes up to $\pm 5^\circ$. The green laser beam is perceived by the human eye 4 times better than a red beam. Its intuitive operating concept and robust construction make it easy to handle. The switchable tilt function, which stops the laser in case of vibrations or shocks, prevents incorrect measurement results. The HV-G can also be used vertically. Complete package with remote control, including laser receiver PDRG60 with mm display, unique in this class!

Technical Details

Working range	Ø 500 m
Operating time	20 h
Weight laser	3000 g
Laser diode / colour	535 nm, class 3R / green
Dimensions laser	215 x 190 x 210 mm
Rotation speed	0; 60; 120; 300; 600 U/min
Protection class	IP65
Self-levelling range	$\pm 5^\circ$
Temperature range HV-G	0 °C to +40 °C
Tolerance (Defined at 25°C in horizontal application)	± 1 mm per 10 m

Scope of supply

Pulsar HV-G, Laser receiver PDRG60 with clamp, Carrying case, Target board, Wall mount, Charger,



MIT DEN BESTEN MESSEN

Remote control, Laser goggles