

NESTLE PULSAR 2S

Fully automatic tilt laser with intuitive operating concept

Product number :16018001



Top features

- Including laser receiver PDRG60 with mm display.
- Set up, switch on, let's go! No tedious adjustment.
- Complete package with receiver and target plate.
- Sturdy aluminium housing
- High visibility

All special features at a glance

- Highest quality workmanship.
- Ideal for tough construction use, thanks to its solid and thick-walled aluminium housing.
- Laser diode used significantly increases visibility indoors.
- Battery charge level indicator in the display.
- The laser can also be operated vertically.

Description

The NESTLE PULSAR 2S is a fully automatic multi-function laser with an intuitive operating concept and a clear function programme and display. Its horizontal or vertical operation recommends this rotating laser for all measuring tasks for indoor and outdoor work. Before rotation, the 2S automatically levels itself; all functions are possible both vertically and horizontally. Complete package with remote control, including laser receiver PDRG60 with mm display, unique in this class!

Technical Details

Working area with receiver	Ø 500 m
Operating time	20 h
Weight	3100 g
Laser diode / colour	635 nm, class 2 / red
Dimensions	215 x 190 x 210 mm
Rotation speed	0; 60; 120; 300; 600 U/min
Protection class	IP65
Self-levelling range	± 5°
Temperature range	-20 °C to +50 °C
Tolerance (Defined at 25°C in horizontal application)	±1 mm per 10 m

Scope of supply

NESTLE PULSAR 2S, Carrying case, Laser receiver, Charger, Target board, Wall mount, Laser goggles, Remote control