#### **LEICA LINO L2G**



# Projects accurately, quickly and easily ideal for interior work

Product number:16725000



#### **Topfeatures**

- Very precise laser lines.
- Self-levelling range ± 4°.
- Exact 90° angle.
- Highly visible green laser beams.

### All special features at a glance

- The LINO L2G projects exact lines for easy and fast work in interior finishing.
- This way you always have your hands free for work.
- In interior design, green light is often more easily perceived by the human eye. The L2G projects green laser beams in laser class 2.
- Whether horizontal, vertical or crossed, the lines are perfectly balanced everywhere on the wall.
- Minor inaccuracies of up to ± 4° when setting up are compensated for automatically.
- With the optional Lino RGR200 receiver, a range of up to 80 metres is possible.
- With triple power supply concept: power supply with Li-Ion battery (included), or included mains adapter or alkaline batteries.

#### **Description**

The Leica LINO L2G is a self-levelling cross line laser that automatically corrects the alignment of lines within  $\pm$  4° when set up. The L2G projects accurately, quickly or easily and is ideal for interior work. The green laser beam of the L2G is perceived by the human eye 4 times better than a red beam and is therefore particularly suitable for drywall construction. The integrated magnet allows the L2G to be attached to the supplied Twist 250 magnetic adapter and attached to magnetic components. The intelligent triple power supply concept makes the Leica LINO L2G universally applicable.

#### **Technical Details**

| Battery             | Li-Ion or 3 x AA      |
|---------------------|-----------------------|
| Accuracy            | ± 0,3 mm/m            |
| Weight              | 530 g                 |
| Laser colour        | L2G = green           |
| Laser class         | 2                     |
| Laser lines         | vertical + horizontal |
| Dimensions          | 110 x 60 x 100 mm     |
| Reach               | up to 35 m            |
| Range with receiver | up to 80 m            |
| Protection class    | IP54                  |



| Self-levelling range | ± 4°        |
|----------------------|-------------|
| Tripod connection    | 1/4" (5/8") |

## **Scope of supply**

Leica LINO L2G-1, Adapter Twist 250, Wall mount UAL130, Charger, Target board, Suitcase, Li-Ion battery